

Electric Vehicle SLA Battery

EVX SERIES

Bosfa EVX Series batteries are designed to have a large amount of stored current discharged between charging sessions, with very heavy non-porous battery plates to withstand repeated major discharging and charging cycle (deep cycles). The Bosfa EVX batteries uses a different chemistry for the plates active paste material, and a slightly stronger electrolyte than normal battery electrolyte, which allows for a much longer life in deep cycle applications.

Application

- Electric Powered Vehicles
- Golf Cars and Buggies
- Wheel Chairs
- Power Tools


- Electric Powered Toys
- Control System
- Vacuum Cleaners
- Medical Equipments
- UPS
- Pvs

General Features




- Sealed and maintenance free operation.
- Non-Spillable construction design.
- ABS containers and covers(UL94HB, UL94V-0) optional.
- Safety valve installation for explosion proof.
- High quality and high reliability.
- Exceptional deep discharge recovery performance.
- Low self discharge characteristic.
- Flexibility design for multiple install positions.

Construction

- ComponentRaw material
- PositiveLead dioxide
- NegativeLead
- ContainerABS
- CoverABS
- SealantEpoxy Resin
- Safety valveEPDR
- TerminalCopper
- SeparatorFibre glass
- ElectrolyteSulfuric acid




Terminal Dimensions



Battery Model	EVX12-20			
Designed Floating Life	> 350 cycles @ 100% DOD			
Capacity(25°C)	20HR(1.1A,1.75V)	10HR(2A,1.75V)	5HR(3.74A,1.75V)	1HR(14.3A,1.75V)
	22AH	20AH	18.7AH	14.3AH
Dimensions	Length	Width	Height	Total Height
	181mm(7.13inch)	76mm(2.99inch)	167mm(6.57inch)	167mm(6.57inch)
Approx. Weight	6.5Kg (14.33 lbs)			
Internal Resistance	Full charged at 25°C: 0.013 Ohm			
Self Discharge	3% of capacity declined per month at (25°C)			
Capacity Affected by Temp.(20HR)	40°C	25°C	0°C	-15°C
	102%	100%	85%	65%
Charge Voltage(25°C)	Cycle use		Float use	
	14.4-15V(-30mV/ °C), max. Current: 6A		13.6-13.8V(-20mV/ °C)	

Electric Vehicle SLA Battery



Constant current discharge ratings-amperes at 25°C

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	3HR	5HR	10HR	20HR
1.60V	78.1	48.6	36.7	22.4	14.2	6.24	3.81	2.13	1.12
1.67V	73.3	46.1	35.3	21.4	14.0	6.00	3.73	2.11	1.08
1.70V	67.2	44.4	34.4	19.4	13.6	5.60	3.65	2.10	1.07
1.75V	65.9	43.1	33.3	18.5	13.0	5.41	3.57	2.08	1.05
1.80V	58.9	41.1	30.3	17.1	12.1	5.20	3.36	2.05	1.03
1.85V	52.0	39.2	27.2	15.8	11.3	5.01	3.15	2.02	1.02

Constant power discharge ratings-watts at 25°C

F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	3HR	5HR	10HR	20HR
1.60V	137	87.8	66.9	40.3	25.7	11.1	6.44	4.27	2.24
1.67V	132	85.6	66.1	39.4	25.5	10.7	6.42	4.24	2.16
1.70V	125	84.7	65.6	36.9	25.0	10.2	6.33	4.21	2.13
1.75V	125	84.4	65.0	35.8	24.6	10.0	6.28	4.16	2.08
1.80V	115	83.2	60.3	34.2	23.2	9.71	6.08	4.11	2.03
1.85V	104	78.9	54.7	32.0	21.8	9.41	5.89	4.05	1.95

